

EUROFLO[®] TWIN WALL HDPE PIPE SN8 400MM OD

PRODUCT SPECIFICATION

NAME:	EUROFLO [®] SN8 400MM PIPE
CODE:	560-400-5.8M
DESCRIPTION:	Heavy duty twin wall external black ribs with smooth grey bore, male/female socketed ends
SIZE:	400mm (-2.4/+1.2) OD, 344mm minimum ID x 5.8M long
MATERIALS:	HDPE high density polyethylene
WEIGHT:	43kg
ASSOCIATED RANGE:	560-400-RBR rubber seal joining rings, 590-400-5.8M Slotted pipe, 521-400- Range of pipe fittings
CERTIFICATION:	EUROFLO [®] SN8 pipe is manufactured according to AS/NZS5065:2005 Polyethylene and polypropylene pipes and fittings for drainage and sewerage standards and has been independently certified – Licence No. WM-032122
STANDARDS:	EUROFLO [®] SN8 pipe meets: <ul style="list-style-type: none"> • AS/NZS2566.1 Buried flexible pipelines - Structural design • AS/NZS2566.2 Buried flexible pipelines - Installation • AS/NZS4404 Land Development and Subdivision Infrastructure • NZTA F3 2.1.7 Specification for pipe construction • NZTA HNH072 Bridge Manual
HYDRAULICS:	Colebrook-White coefficient k [mm] = 0.003-0.015, Mannings roughness coefficient (n) 0.008-0.009
INSTALLATION:	Install according to AS/NZS2566.2 Buried Flexible Pipes
LIFESPAN:	AS/NZS5065:2005 testing is set at 50 years but mentions that it can be logically expected to be well in excess of 100 years
APPLICATIONS:	Gravity pipelines for stormwater and wastewater – greenfield and brownfield. Highway drainage, roading culverts, farm and forestry culverts, and general stormwater management including soak pits and wells.

PIPE PROFILE:

